

Refine Search

Search Results -

Terms	Documents
L20 same shortened	0

Database:

US Pre-Grant Publication Full-Text Database
 US Patents Full-Text Database
 US OCR Full-Text Database
 EPO Abstracts Database
 JPO Abstracts Database
 Derwent World Patents Index
 IBM Technical Disclosure Bulletins

Search:

L24

Search History

DATE: Tuesday, December 25, 2007 [Purge Queries](#) [Printable Copy](#) [Create Case](#)

Set Name Query

side by side

Hit Count

Set Name

result set

DB=USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=OR

L24	L20 same shortened	0	L24
L23	L20 same euclid\$	0	L23
L22	L20 same l1	0	L22
L21	L20 same position	3	L21
L20	L19 same encod\$	36	L20
L19	L8 same polynomial same remainder	153	L19
L18	L16 same polynomial	3	L18
L17	L16 same polynomial same remainder	0	L17
L16	L12 same encod\$	1859	L16
L15	L14 and l10	0	L15
L14	L2 same position	13	L14
L13	L12 same l2	1	L13
L12	predetermined adj1 position	212310	L12
L11	L10 and l2	3	L11
L10	L8 same remainder same polynomial	153	L10
L9	L8 same l2	3	L9

<u>L8</u>	galois adj1 field	2296	<u>L8</u>
<u>L7</u>	L2 same remainder same polynomial	5	<u>L7</u>
<u>L6</u>	L5 same l2	0	<u>L6</u>
<u>L5</u>	remainder adj1 polynomial	306	<u>L5</u>
<u>L4</u>	L3 same polynomial	8	<u>L4</u>
<u>L3</u>	L2 same reed-solomon	19	<u>L3</u>
<u>L2</u>	L1 same encoding	112	<u>L2</u>
<u>L1</u>	shortened near3 code	898	<u>L1</u>

END OF SEARCH HISTORY

[First Hit](#) [Fwd Refs](#)[Previous Doc](#) [Next Doc](#) [Go to Doc#](#)☐ [Generate Collection](#) [Print](#)

L4: Entry 4 of 8

File: USPT

Dec 3, 2002

DOCUMENT-IDENTIFIER: US 6490243 B1

TITLE: Information data multiplex transmission system, its multiplexer and demultiplexer and error correction encoder and decoder

Brief Summary Text (51):

(21) In the configuration of (20), the error correction encoding means includes: an encoder main body for conducting error correction encoding processing on the second information data which has been shift-input by using a shortened Reed-Solomon code; and an order reversal means for shift-inputting a plurality of information elements forming the second information data to the encoder main body in descending order of term degree of an information polynomial and causing the information elements to be subjected to error correction encoding processing.

CLAIMS:

9. A transmitting apparatus comprising: an error detection code addition means for adding an error detection code to first information data to be transmitted and outputting second information data; an error correction encoding means for encoding the second information data output from said error detection code addition means using an error correction code formed of a shortened Reed-Solomon code and outputting third information data, wherein said error correction encoding means further comprises: an encoder main body for conducting error correction encoding processing on the second information data which has been shift-input by using a shortened Reed-Solomon code, and an information data input means for shift-inputting a plurality of information elements forming said second information data to said encoder main body in descending order of term degree of an information polynomial and causing the information elements to be subjected to error correction encoding processing; and a header addition means for adding a control header having control information representing a transmission form of said information data inserted therein to the third information data output from said error correction encoding means.

17. An information data transmitting apparatus for use in a data communication system, comprising: means for adding an error detection code to a first variable-length information data to obtain a second variable-length information data; error correction encoding means for encoding the second variable-length information data with a shortened Reed-Solomon code to obtain a third variable-length information data; wherein the error correction encoding means comprises a shift register having a shift-inputting means for shift-inputting a plurality of information elements that constitute the second variable-length information data and that are formed as an information polynomial, the shift-inputting means inputting the information elements in descending order of term degree of the information polynomial; and means for transmitting the third variable-length information data to a reception side for reproduction of the first variable-length information data.

[Previous Doc](#) [Next Doc](#) [Go to Doc#](#)

[First Hit](#) [Fwd Refs](#)[Previous Doc](#) [Next Doc](#) [Go to Doc#](#)☐ [Generate Collection](#) [Print](#)

L9: Entry 1 of 3

File: USPT

Apr 4, 2006

DOCUMENT-IDENTIFIER: US 7024616 B2

TITLE: Method for encoding/decoding error correcting code, transmitting apparatus and network

PRIOR-PUBLICATION:

DOC-ID

DATE

US 20010053225 A1

December 20, 2001

Description Paragraph (96):

When code subblocks 10-i for the C1-encoding comprise 16 subblocks each having a length of 255 bytes corresponding to each of 16 rows, either of the following two can be employed as the C1 code: an eight-error-correcting RS code (255, 239); and an eleven-error-correcting shortened BCH code (2040, 1919) based on Galois field (2048).

Description Paragraph (99):

In FIG. 4, with m set to one, 255 code subblocks 20-j for the C2-encoding exist, wherein each code subblock has its bits arranged serially in the column direction. In this case, either of the following two can be employed as the C1 code: a single-error-correcting shortened RS code (18, 16); and a double-error-correcting shortened BCH code (144, 128) based on Galois field (256).

Description Paragraph (100):

Alternatively, when m is set to two to create 128 code subblocks 20-j for the C2-encoding, and one column lacking in the last code subblock 20-128 is regarded virtually as zero, either of the following two may be employed as the C2 code: a double-error-correcting shortened RS code (36, 32); and a triple-error-correcting BCH code (288, 261) based on Galois field (512).

Description Paragraph (101):

Further alternatively, when m is set to eight to create 32 code subblocks 20-j for the C2-encoding, and one column lacking in the last code subblock 20-32 is regarded virtually as zero, either of the following two may be employed as the C2 code: an eight-error-correcting shortened RS code (144, 128); and an eleven-error-correcting shortened BCH code (1152, 1031) based on Galois field (2048).

CLAIMS:

3. A method for encoding an error correcting code according to claim 2, wherein: said A is set to 1; said B is set to 128; said C is set to 238; said D is set to 15/14; said E is set to 255; said J is set to 19; said L is set to 1; said P is set to 112; said Q is set to 8; and said R is set to 15/14; said outer code .LAMBDA. comprises either an eight-error-correcting Reed-Solomon code on Galois field, or an eleven-error-correcting shortened BCH code based on Galois field; and said inner code .PSI. comprises either an eight-error-correcting shortened Reed-Solomon code on Galois field, or an eleven-error-correcting shortened BCH code based on Galois field.

10. A method for encoding an error correcting code according to claim 9, wherein: said A is set to 1; said B is set to 128; said C is set to 238; said D is set to 15/14; said E is set to 255; said F is set to 16; said G is set to 144; said H is set to 1; said J is set to 255; and said L is set to 1; said outer code .LAMBDA. comprises either an eight-error-correcting Reed-Solomon code on Galois field, or an eleven-error-correcting shortened BCH code based on Galois field; and said inner code .PSI. comprises either a

single-error-correcting shortened Reed-Solomon code on Galois field, or a double-error-correcting shortened BCH code based on Galois field.

11. A method for encoding an error correcting code according to claim 9, wherein: said A is set to 1; said B is set to 112; said C is set to 238; said D is set to 15/14; said E is set to 255; said F is set to 16; said G is set to 128; said H is set to 1; said J is set to 255; and said L is set to 1; said outer code .LAMBDA. comprises either an eight-error-correcting Reed-Solomon code on Galois field, or an eleven-error-correcting shortened BCH code based on Galois field; and said inner code .PSI. comprises either a single-error-correcting shortened Reed-Solomon code on Galois field, or a double-error-correcting shortened BCH code based on Galois field.

[Previous Doc](#)[Next Doc](#)[Go to Doc#](#)

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



INTERNATIONAL BUREAU OF PATENT COOPERATION
358, RUE DE LA PATENTE, CHAMBELEN, SUISSE

(43) International Publication Date
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number
WO 2005/008900 A1

- (51) International Patent Classification⁷: H03M 13/15
(21) International Application Number: PCT/IB2004/002623
(22) International Filing Date: 21 July 2004 (21.07.2004)
(25) Filing Language: English
(26) Publication Language: English
(30) Priority Data: 0308868 21 July 2003 (21.07.2003) FR

(71) Applicant (for all designated States except US): CANON KABUSHIKI KAISHA (JP/JP); 3-30-2, Shimomarucho, 3-chome, Ohta-ku, Tokyo (JP).

- (72) Inventors; and
(75) Inventors/Applicants (for US only): PIRET, Philippe [BE/FR]; 4, boulevard des Métairies, F-35510 Cesson-Sevigne (FR). LE BARS, Philippe [FR/FR]; 12, rue du Manoir, F-35235 Thorigné-Fouillard (FR). LEHOBEY, Frédéric [FR/FR]; 185, rue des Fougères, F-35700 Rennes (FR).

(74) Agent: PETIT, Maxime; Santarelli, 14, avenue de la Grande Armée, F-75017 Paris (FR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:


- of inventorship (Rule 4.17(iv)) for US only
— of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report

[Continued on next page]

(54) Title: INFORMATION ENCODING BY SHORTENED REED-SOLOMON CODES



(57) Abstract: The present invention concerns an encoding method in which encoding is performed of any information word a of length k in the form of a word v belonging to a Reed-Solomon code C of dimension k' and length n' (with $n' \cdot k' = n \cdot k$) such that the components of v' situated in $(n' \cdot n)$ arbitrary predetermined positions be systematically equal to respective predetermined constants (for example, all zero). The possibility then exists of deleting those components of fixed value to obtain a word v of length n belonging to a code C , which thus constitutes a code that is shortened with respect to code C . The invention also relates to devices and apparatuses adapted to implement the encoding method. The invention may be used for encoding by means of an algebraic geometric code, when such encoding may be implemented by encoding by means of a plurality of shortened Reed-Solomon codes.

[First Hit](#)[Previous Doc](#)[Next Doc](#)[Go to Doc#](#)

End of Result Set

☐ [Generate Collection](#) [Print](#)

L13: Entry 1 of 1

File: EPAB

Jan 27, 2005

DOCUMENT-IDENTIFIER: WO 2005008900 A1

TITLE: INFORMATION ENCODING BY SHORTENED REED-SOLOMON CODES

Abstract Text (1):

The present invention concerns an encoding method in which encoding is performed of any information word a of length k in the form of a word v' belonging to a Reed-Solomon code C of dimension k' and length n' (with $n'-k'=n-k$) such that the components of v' situated in $(n'-n)$ arbitrary predetermined positions be systematically equal to respective predetermined constants (for example, all zero). The possibility then exists of deleting those components of fixed value to obtain a word v of length n belonging to a code C , which thus constitutes a code that is shortened with respect to code C . The invention also relates to devices and apparatuses adapted to implement the encoding method. The invention may be used for encoding by means of an algebraic geometric code, when such encoding may be implemented by encoding by means of a plurality of shortened Reed-Solomon codes.

[Previous Doc](#)[Next Doc](#)[Go to Doc#](#)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 January 2005 (27.01.2005)


PCT

(10) International Publication Number
WO 2005/008900 A1

- (51) International Patent Classification: **H03M 13/15**
- (21) International Application Number: PCT/IB2004/002623
- (22) International Filing Date: 21 July 2004 (21.07.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0308868 21 July 2003 (21.07.2003) FR
- (71) Applicant (for all designated States except US): CANON KABUSHIKI KAISHA [JP/JP]; 3-30-2, Shimomaruko, 3-chome, Ohia-ku, Tokyo (JP).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): PIRET, Philippe [BE/FR]; 4, boulevard des Métairies, F-35510 Cesson-Sevigne (FR). LE BARS, Philippe [FR/FR]; 12, rue du Manoir, F-35235 Thorigné-Fouillard (FR). LEHOBEY, Frédéric [FR/FR]; 185, rue des Fougères, F-35700 Rennes (FR).
- (74) Agent: PETIT, Maxime; Santarelli, 14, avenue de la Grande Armée, F-75017 Paris (FR).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PI, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SI, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CH, CG, CI, CM, GA, GN, GQ, GW, MI, MR, NE, SN, TD, TG).
- Declarations under Rule 4.17:**
— of inventorship (Rule 4.17(iv)) for US only
— of inventorship (Rule 4.17(iv)) for US only
- Published:**
— with international search report

[Continued on next page]

(54) Title: INFORMATION ENCODING BY SHORTENED REED-SOLOMON CODES



(57) Abstract: The present invention concerns an encoding method in which encoding is performed of any information word a of length k in the form of a word v belonging to a Reed-Solomon code C of dimension k' and length n' (with $n'-k' = n - k$) such that the components of v' situated in $(n'-n)$ arbitrary predetermined positions be systematically equal to respective predetermined constants (for example, all zero). The possibility then exists of deleting those components of fixed value to obtain a word v of length n belonging to a code C , which thus constitutes a code that is shortened with respect to code C . The invention also relates to devices and apparatuses adapted to implement the encoding method. The invention may be used for encoding by means of an algebraic geometric code, when such encoding may be implemented by encoding by means of a plurality of shortened Reed-Solomon codes.

10



Europäisches Patentamt
European Patent Office
Office européen des brevets

11 Publication number:

0 158 510
A2

12

EUROPEAN PATENT APPLICATION

21 Application number: 85302362.0

22 Date of filing: 03.04.85

51 Int. Cl.: H 03 M 13/00
G 06 F 11/10

30 Priority 06.04.84 US 597538

43 Date of publication of application:
16.10.85 Bulletin 85/42

64 Designated Contracting States:
CH DE FR GB LI NL SE

71 Applicant AMPEX CORPORATION
401 Broadway
Redwood City California 94063(US)

72 Inventor Stenarson, Roger M.
4000 N.W. Hill Dr. Apt 12
Corvallis Oregon 97330(US)

74 Representative: Horton, Andrew Robert Grant et al,
BOULT, WADE & TENNANT 27 Farnhill Street
London, EC4A 3DF(GB)

64 Error detection and correction in digital communication systems.

77 An error detection and correction system for locates and corrects double errors in a received data block word digitally encoded in a Reed-Solomon code (n,K) as coefficient terms of an n-order codeword polynomial in the form

$$C(x) = \sum_{i=0}^{n-1} c_i x^i$$

where the coefficients are powers of the primitive α of a Galois field, which codeword is divisible by a code generator polynomial in the form of a product of a plurality of different factors in the form $(x + \alpha^i)$. Four syndrome signals are derived each corresponding to a respective first order syndrome equal to the remainder upon dividing a received data block word by a respective factor. An error locator responsive to the four syndrome signals derives a reference signal corresponding to the position h of a reference term in the received data block word spaced relative to the two terms containing errors, and a relative position signal k corresponding to the number of terms by which the terms containing the errors are spaced from the reference term. An error solution circuit responsive to the four syndrome signals produces first and second error solution signals corresponding to the differences between the respective received terms containing the errors and the corresponding terms α^h

encoded. An error correction circuit adds the error solution signals to the received data block at the proper places to reproduce the encoded codeword. A fifth syndrome signal may be used to determine if there are more than two errors. Two syndromes may be used to correct single errors.

